

HOLORIB DECKING WITH
CONCRETE SLAB

SPACE IN HOLORIB TO
BE INFILLED WITH MINERAL
WOOL OR INTUMESCENT FOAM

SEALANT

DRY PACKED WITH MINERAL
WOOL IF A GAP IS PRESENT.

SEALANT

50 x 50 WFSL INTERNAL
ANGLE RIVETED TO PANELS
& HILTI FIXED TO SLAB.

PIR / MINERAL WOOL
INSULATED WALL PANEL.

STEEL BASE CHANNEL, TO
MATCH WALL PANEL FINISH,
FIXED TO FLOOR SLAB USING
HAMMER HIT. FIXINGS.
CHANNEL SUITABLY SEALED &
RIVETED TO PANELS.

MASTIC / SILICONE SEAL.

WATER RESISTANT
SEALS.

INTUMESCENT SEALS.



SPECIALIST INSULATION TECHNICIANS
TO THE WORLDWIDE CATERING, FOOD
PROCESSING & COLDSTORAGE INDUSTRIES

UNIT 5a, SEVERNBRIDGE INDUSTRIAL ESTATE
SYMONDSCLIFFE WAY, PORTSKEWETT,
CALDICOT, MONMOUTHSHIRE, NP26 5PW

TEL: 00 44 1633 882048 ;
FAX : 00 44 1633 882034
E-MAIL ; MRGIL42070@aol.com

TITLE;
TYPICAL DETAIL; FIRE PANELS;
TYPICAL SECTION THROUGH
PARTITION WALL.

DRG. No; TDFR ~ 11